

# AXCELLA 500 SX 10W-40

## Premium Performance Semi Synthetic Engine Oil

Axcella 500 SX SAE 10W-40 is a high performance semi synthetic engine oil that exceeds the latest industry performance standards required in today's gasoline and diesel automobile engines. Actively maintains overall engine cleanliness preventing the build up of harmful deposits, sludge, wear and varnish in a wide range of temperatures.

---

## Benefits

- Enhanced thermal and oxidation stability
- Excellent anti-wear properties
- Effective deposits control
- High viscosity index and shear stability protecting engine parts at high operating temperatures and reducing oil consumption

---

## Applications

- High performance, turbo-charged gasoline and diesel engines, as well as older normally aspirated models, of passenger cars, light trucks and vans

## AXCELLA 500 SX 10W-40

Premium Performance Synthetic Engine Oil

# Specifications

### AXCELLA 500 SX 10W-40

#### Meets the following Specifications

API SN	✓
ACEA A3/B4-16	✓
MB 229.3	✓
RN710 / PSA B71 2300	✓

#### Typical properties

10W-40

Test parameters	Method	
Viscosity @ 40 °C, cSt	ASTM D 445	92.1
Viscosity @ 100 °C, cSt	ASTM D 445	14.4
Viscosity Index	ASTM D 2270	162
Flash Point, °C	ASTM D 92	220
Pour Point, °C	ASTM D 97	-30
Density @ 15°C, Kg/l	ASTM D 4052	0.875
TBN, mg KOH/g	ASTM D 2896	7.9

Above characteristics are mean values given as information. They do not constitute a specification.

## Health and safety

This lubricant is unlikely to produce any significant health or safety hazard when used in the application it has been designed for and according to the recommendations provided in the Material Safety Data Sheet. MSDS are available upon request through your sales advisor.

When disposing of used oil, please observe all current regulations and protect the environment.