



MULTI TSG

Premium fifth wheel grease

Product Overview

MULTI TSG is a specific lubricating grease based on mineral oil with a very high base oil viscosity value, lithium/calcium soap, solid lubricant and EP additives. This grease offers a good protection against corrosion and a good adhesiveness thanks to polymer.

This grease has been formulated specifically for fifth wheel.

Properties & Benefits

- Good corrosion protection
- Extreme pressure grease
- Good water resistance

Health and Safety

This lubricant is unlikely to produce any significant health or safety hazard when used in the application it has been designed for and according to the recommendations provided in the Material Safety Data Sheet. MSDS are available upon request through your sales advisor.

When disposing of used oil, please observe all current regulations and protect the environment.

MULTI TSG		
Typical properties		
Test parameters	Method	
NLGI Grade	ASTM D 217	2
Thickener		Lithium / Calcium
Base fluid		Mineral Oil / Polymer
Texture		Smooth
Colour	Visual	Black
Base Oil Viscosity @ 40 °C, mm2/s	ASTM D 7152	1032
Base Oil Viscosity @ 100 °C, mm2/s	ASTM D 7152	51
Dropping point	IP 396	>170 °C
Penetration 60 strokes	ISO 2137	265 – 295
4-ball weld load	ASTM D 2596	>500Kg
Water resistance at 90 °C	DIN 51807:1	0
Water Wash Out at 79 °C	ISO 11009	<5%
Emcor dist water	ISO 11007	0 – 0
Emcor salt water	ISO 11007	2 - 0
Density @ 15 °C, Kg/m3	IP 530	899
Temperature range		-10 °C to +120 °C

Above characteristics are mean values given as information. They do not constitute a specification.